

## INSTRUCTIONS TO APPLY DECAL

### STEP ONE.

Clean the surface you going to apply the decal to, removing existing grime or greasiness. Surface must be clean, dry and free of any waxy/silicone products such as mr sheen, etc.

### STEP TWO

Place decal against surface in desired position and mark on either side using a removable marker - eg wax pencil, make sure marks are equal height - check with tape measure - and line up with pen line drawn on decal. The vertical line on the decal shows the middle of the sticker, you may want to mark the centre of the surface area, so the decal can line up to this. Make sure that any marks will not be under where the decal is applied.

### STEP THREE

Peel off the backing paper from the decal, leaving the lettering and front masking tape. Hold decal just off surface and line up with your marks - so it is straight. Once straight touch decal against surface on one edge and push down along the decal to the other side. A plastic squeegee is usually used to apply decal, if you do not have one a credit card or similar plastic object could be used....just don't break it!

### STEP FOUR

Rub very hard over the letters. The edge of the squeegee can be used to push air out from under the sticker.

### STEP FIVE

Peel off the front masking tape, which covers the lettering, very slowly - pulling back hard against the surface. If letters do not stick, stop and repeat step four.

### STEP SIX

Once the top masking tape has been removed, remove any air bubbles remaining between letters and surface by pin pricking the letters and force air out by rubbing with your finger.

Any questions or problems feel free to contact the office on the below details.